

PLANETARY MIXERS SERIES

MIX SF



A

A: Details of the hydraulic group and of the automatic greasing system




B

B: Internal of the mixing tank
C: Fully equipped mixing machine

Intensive mixing system distinguished by its simultaneous rotating movement on the vertical axis of the central mixing arms and of the peripheral arms that bring the material to the mixing blades. Ideal for a low water/cement ratio mixture (semi-dry/dry). It is able to perfectly amalgamate in relatively short times traditional materials or even lighter materials as expanded clay. The discharge action, due to the use of maximum 3 discharge doors on the bottom of the mixer, is achieved in a few seconds. It can be supplied with or without loading hopper (stationary or mobile).

TECHICAL DATA		SF2200	SF2400	SF2850	SF3400	SF4000	SF8000	SF9000	SF10000
Volumetric capacity of the tank	L	750	1125	1500	1875	2250	3000	3750	4500
Soft concrete output by cycle	L	600	900	1200	1500	1800	2400	3000	3600
Vibrated concrete output by cycle	L	500	750	1000	1250	1500	2000	2500	3000
Mixing arms	N°	3	3	3+3	3+3	3+3	2+2+2	3+3+3	3+3+3
Peripheral arms	N°	1+1	1+1	2	2	2	3	3	3
Power of the mixing motor	KW	22	30	45	55	75	90	110	132
Power of the loading hopper motor	Kw	12/15	12/15	18,5/22	18,5/22	18,5/22	22/30	37/45	37/45
Ascending/descending speed of the loading hopper	m/min	20/40	20/40	20/40	20/40	20/40	24/48	24/48	24/48

The specifications and the features of the product may be subject of variations without previous notice.



C